

JDre

Nitrogen Compressor Systems

HPCOM Series

Robust, reliable and efficient

Description

Following extensive bench mark testing and comparison, Cinpres UK Limited selected German Sauer compressors for its HPCOM series.

The compressors are all 4 stage air cooled electric driven high pressure reciprocating piston type. They have directly coupled motors, (i.e. no belt drive) and are engineered for long life under continuous production conditions. Oil carry over is very low and service intervals are 2,000 hrs.

The HPCOM series has output flow rates between 350 and 1070NI/ min at pressures up to 350 BarG. The compressors are housed in steel cabinets for optimal cooling air flow and low noise emissions.

The units can be supplied in either single or duplex configuration. Duplex systems enable the second compressor to be used as a standby or to provide increased output.

Features and Benefits


- Robust engineered for consistent operation under production conditions
- **Reliable** long intervals between services (2000 hrs)
- Efficient low oil consumption and noise emissions
- Competitive investment when related to the higher nitrogen outputs and the lower maintenance costs




For details on our whole product range or to request a brochure, please visit our website: www.cinpres.com

General Information


HPCOM 21, 32 and 60





High Pressure Nitrogen Compressor System

HPCOM T Series



Specifications

| Model | Max. output Pressure (BarG) | Max. output (NL/min) | Power Voltage (3P+N+E) | Power Consumption (KW) | Weight (Kg) |
|---------|-----------------------------------|-------------------------|------------------------------|------------------------------|----------------|
| HPCOM21 | 350 | 335 | 380 VAC | 11 | 700 |
| HPCOM32 | 350 | 510 | 380 VAC | 18 | 730 |
| HPCOM60 | 350 | 1000 | 380 VAC | 21 | 770 |

Gas Connections

| Gas Inlet: | 1/2" ISO standard parallel female (minimum ID 12.5mm) |
|-------------|---|
| Gas Outlet: | 1/4" ISO standard parallel female |

Standard Connections Kits

HPCOM: 1/4" Flexible Hose-2M Length with connector (2pcs)

Duplex Systems (D) with 2 compressors side by side with 2 controllers are available for each model



Cinpres UK Limited, Unit 4, Meridian House, Road One, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QG, United Kingdom

Tel: +44 121 270 6857 Email: sales@cinpres.com Web: www.cinpres.com